

HOURS



YEARS

WARRANTY







1-10V

DIMMABLE



NEXT DAY DELIVERY



The Hyskeir Pro Highbay has been re-designed to focus on **sustainability.** The improved Hyskeir Pro 4 Highbay has been increased to 165lm/W. Keeping delivered lumens the same to mimic traditional HID outputs whilst lowering system wattages to give the very best energy savings and drive us towards carbon neutrality. A lifetime of up to 120,000 hours ensures your lighting is reliant and sustainable for many years to come. And packaging volume has been reduced by 35-45% using fully recyclable cardboard.

An all in one solution for your highbay requirements.

HIGHBAY PRO 4



Order Code: IND170v4-C10

Photometric Data

Lumens	25500
Colour Rendering Index (CRI)	80-89
Adjustable CCT	No
Stroboscopic effect value SVM	0.4
LPW (lm/W)	165
Colour Temperature (K)	5000-5000
SDCM	SDCM3
Light Distribution	Symmetric
Lens / Reflector	None

Life Data

Rated Life (Hrs)	Ta = 25C	Ta = Tmax
	120000	80000
I	Ta = 25C	Ta = Tmax
Lumens Maintenance (Hrs) —	B50	B50
L70	120000	80000
L80	80000	-
L90	-	-


Electrical Data

LED Power	146-146
Microwave Sensor	No
Light Sensor	No
PIR Sensor	No
Short Circuit Protection	Yes
Thermal Overload Protection	Yes
Flicker Free	Yes
Input Current (mA)	650-1300
No. Per B16 Breaker	6
No. Per C16 Breaker	11
Input (W)	155
Input (V)±10%	120-277
Voltage Type	AC
Power Factor	0.97
THD (%)	5
Electrical Class	1
Type of Wiring	Ending
1-10V Dimming	Yes

Physical Data

5
Yes
-30-40
IP65
Pendant
Black
Aluminium
None
145
262
LED exchangeable
Yes
IK10







Order Code: IND170v4-C10

Accessories	
ACS137 - 60° Aluminium Reflector	
ACS138 - 90° Aluminium Reflector	
ACS142 - 90° Polycarbonate Reflector	
ACS193 - Large 90° Polycarbonate Reflector	
ACS140v2 - Programming Remote for SMD Microwave Sensor	
ACS141 - Surface Mounting Bracket	

Logistical Data

Gross Weight (kg)	3.2
Packaging Length (mm)	275
Packaging Width (mm)	275
Packaging Height (mm)	168